

R2SD4-12

Power Handling

250 Watts RMS / 500 Watts Max.

**Dual Voice Coil
Subwoofer 30 cm**

Technical Specifications

Impedance	Zn	2 x 4 Ohms
Voice Coil Diameter	Ø	50 mm
Voice Coil Winding Height		26,9 mm
Max. Linear Excursion	Xmax	+/- 5 mm
Max. Mechanical Excursion	Xmax (Peak)	+/- 20 mm
Cone Area	Sd	535 cm ²
Moving Mass	Mms	172,8 g
DC Resistance	Re	2 x 3,4 Ohms
Resonance Frequency	Fs	30,3 Hz
Mechanical Q-Factor	Qms	7
Electrical Q-Factor	Qes	0,72
Total Q-Factor	Qts	0,65
Equivalent Air Volume	VAS	65,4 L
VC Inductance	Le	4,2 mH
Flux Density	B/L	17,6 N/A
Efficiency 1W/1m	SPL	85 dB

Recommended Enclosure

Sealed Box	
Sealed Volume:	25,5 L
-3 dB Rolloff (F3):	44 Hz

Recommended Enclosure

Ported Box	
Vented Volume:	50,7 L
Port Diameter:	100 mm
Port Area:	80 cm ²
Port Length:	30 cm
Tuning Freq. (Fb):	40 Hz
-3 dB Rolloff (F3):	34 Hz

Mechanical Components

- Steel Basket
- Polypropylene Cone
- Foam Surround
- Polypropylene Dustcap
- Single Spider
- Aluminium Voice Coil Former

Dimensions & Weight

External Diameter:	329 mm
Mounting Diameter:	285 mm
Mounting Depth:	92 mm
Shipping Weight:	5,9 kg

