

SH×352 SH×402 SH×462 SH×522 SH×652 SH×692



SHX HIGH POWER COAXIAL SPEAKER

CONGRATULATIONS!

You now own an EXCURSION SHX Series High Power Coaxial Speaker, the product of an uncompromising design and german engineering philosophy. A product made from Car Audio fanatics who truely believe in the relentless pursuit of perfection.

EXCURSION speakers are the result of several decades of product improvements, competition, innovation and highest quality parts and control standards in industry. When properly installed these speakers will provide you with many years of listening pleasere and are the perfect balance between high fidelity, extreme performance and long-lasting reliabilty.

Should your speaker ever need a service, Please record your information on the following lines to refer to in the event that you may need it later.

Dealer's Name
Date of Purchase
nstallation Shop
nstallation Date

At EXCURSION Intl. we are confident you will have many years of outstanding enjoyment from your high performance investment. For maximum performance we recommend that you have your new EXCURSION SX Speakers installed by an exclusive Authorizied EXCURSION Dealer

To learn more about EXCURSION, please visit us on the World Wide Web at

http://www.excursion.us

CAUTION!

Continuous exposure to sound pressure levels in excess of 100dB can cause permanent hearing loss. EXCURSION Speakers are capable of producing sound pressure levels well over 170dB. Please observe all local sound ordinances while listening to your EXCURSION System. EXCURSION Intl. acceptss no liability for hearing loss, bodily injury, or property damage due to the result of use or missuse of this product.



EXCURSION SHX SPEAKER FEATURE

2-Layer Wool Fibre Composite Cone: For the Sound Quality of our SHX advanced high efficient OEM Upgrade Design we have researched carefully for an even lighter vital wool fibre material. In composite with our proven paper former this is the most natural material and choice. With a decrease aprox 10% in weight and an increase of stiffness and the vitality of the cone surface our SHX cone Design step up the already outstanding fine dynamic and resolution of our well known SX Series. Together with a 25% stronger motor SHX set an even higher benchmark for the best OEM Upgrade Design for speakers up to 100 RMS/300 Watt Music Power Handling.

Phased Plug Dustcap Design: effect in higher resolution of vocal mid section at none axial or difficult OEM speaker position, while reducing unwanted distortion and losses.

DIN sized fully vented Steel Basket: The EXCURSION steel baskets are DIN sized for easy OEM Upgrade Replacement. Their symmetrical design together with the stamped EXCURSION logos ensure outstanding static, aerodynamic and stiffness. Coated with black antivibration colour the baskets are acoustical deaden to provide best results. We at EXCURSION took especially care of maximum cooling of voice coil. All baskets are symmetrical vented below the spider for maximum heat transfer, knowing that a cool voice coil is able to take more power and handle more power.

30hm Voice Coils: For our SHX advanced high efficient OEM Upgrade Design we have researched to lower the Voice Coil impedance to 30hm, which step up in aprox 25% more power supply from most amplifiers on the market. From the decrease of impdeance we could benefit and balance with thicker copper wire of voice coil and step up once more in higher power handling. But as we are EXCURSION and the best is not enough, we have pole piece vented all motors for extra cooling and are setting new standards with taking over aluminium former top ventilation technology for all SHX component and coaxial speaker from our SHX High Power Subwoofers.

Pure Silk, Soft Dome Tweeter: The outstanding performance of the EXCURSION Tweeters set the biggest difference to the competitors in the Car Audio market. Using the finest materials of Pure silk with perfect EXCURSION lineartiy, the EXCURSION Tweeters love to get compared with the leading audiophile's in the world.

One way Hide Away Plug&Play Crossovers: We at EXCURSION have designed the smartest high quality crossover solution possible. We focus on the most important and are using best parts and cables which can get plugged in various combinations. Compareable to the Voice Coil we could increase the copper wire diameter of our magnet core low pass coil caused of lowered 30hm impedance and step once more up in Power Handling. With our Single way crossovers inliners and a range of level resistors the system is prepared for demands of Bi-Wiring and level tuning on demand.

Pre-Installation Instructions:

It is recommend that you have your new EXCURSION SHX Series Automotive Speakers professionally installed by your authorizied EXCURSION dealer. This will ensure use of proper installation techniques and materials and save much time and efforts. If you choose to perform your own installation, the following instruction will give you direction toward making your purchase complete. Read the following information and precautions carefully. Failure to follow the stated precautions may result in personal injury or damage the audio system or vehicle.

- A.) Always make sure the speaker will easily fit into the intended mounting location and that there is adequate cavity depth to accept the magnet structure.
- B.) Check for adequate clearance between speaker and window, window crank, power window mechanism, seat, glove box, rear deck torsion bars and other items which may interfere with the speaker's mounting. This is especially important if any hole cutting is required. Complete speaker, mounting size and depth requirements can be found next to these instructions. A good way to confirm speaker place meet on a door or body panel is to place the speaker's die cast mounting ring onto the surface. Check for a flat mounting surface, free from all obstruction.
- C.) The method of installation choosen and level of execution will effect the overall performance of the EXCURSION Speakers. Thread each installation step with a high degree of attention.
- D.) Do not mount the speaker where water may splash the woofer cone. A plastic cup or some heavy gauge plastic sheeting may be needed in some locations that are exposed to moisture from behind the body panel.
- E.) Care must be taken to prevent low frequency cancelation caused by air leakage between the front and rear of the speaker (such as when mounted on a curved or uneven surface, or when mounted in an oversized hole)
- F.) Mounting panel reinformcement may be necessary in some cases in order to prevent surface flex. This can be achieved by mounting the speaker on a metal or wooden sub-baffle behind the body or door panel.

 Consult an installation specialst for further direction.



G.) Unless you are replacing existing speakers of same size, mounting locations will have to be cut into the doors, body panels or rear deck. In some cases speaker mounting holes will be precut in the doors, bodypanels, or rear deck steel. Due to their structural integrity and accessibility. These precut mounting holes should be used whenever possible.

IMPORTANT: Never cut any metal that is an integral part of an automobile's safety or structural support system.

NOTE: EXCURSION strongly recommends that you operate the complete audio system at low volume before final installation of your SX Series Automotive Loudspeakers. This will allow a trial listening test before securing the loudspeakers into their mounting locations.

CAUTION: Make sure that all speaker wiring is fully protected from cutting or wear. Any short circuits developing as a result could severaley damage the radio unit or amplifier. Make sure that all speaker wires easily reach the speaker terminals without stress on the wire or connectors.

PREPARING FOR INSTALLATION

Note: The tools listed below may be required for proper installation.

- * An electtric drill with drill bits
- * Phillips-head and standard screwdrivers
- * Crimping tool and needle-nose pliers
- * Silicon sealant or closed cell weather-stripping
- * Metal file, Hole saw, Tin Snips, Wire strippers

INSTALLATION PRECAUTIONS

Note: Proceed only if you are a qualified installer otherwise let your dealer do it.

- * Always wear protective eyewear when using tools
- * Turn OFF all stereo and other electrical devices before you begin
- * Disconenect the (-) negative lead from your vehicle's battery.
- * Keep the speakers in the package until final installation.
- * Locate fuel lines, brake lines, oil lines, electrical cables when planning installation.
- * Check to see clearance behind the mounting surface before installing speakers.
- * When running speaker wires through sheet metal, be sure to use gromments to properly insualte the wires from metal edges.

SPECIFICATIONS FOR EXCURSION SHX SERIES SPEAKERS

(Due to Constant Improvements, Specifications and Parameters are subject to change without notice)

Model	Size	Nominal Impedance	Frequency Response	Sensitivity 1W/1M	Magnet Size	Mounting Depth
SHX-352	3.5"	30hm	70Hz-20KHz	87dB	5 oz.	41mm
SHX-402	4"	30hm	60Hz-20KHz	88dB	10 oz.	51mm
SHX-522	5.25"	30hm	55Hz-20KHz	89dB	10 oz.	54mm
SHX-652	6.5"	3Ohm	50Hz-20KHz	90dB	12.5 oz.	60mm
SHX-462	4x6"	3Ohm	60Hz-20KHz	88dB	10 oz.	53mm
SHX-692	6x9"	3Ohm	45Hz-20KHz	90dB	20 oz.	85mm

Note: Grills are included at 6x9" models



EXCURSION LIMITED WARRANTY POLICY

EXCURSION Intl. offers limited warranty on EXCURSION products under normal use on the following terms:

EXCURSION Speakers are to be free of defects in material and workmanship for a period of one year.

This warranty applies only to EXCURSION products sold to consumers by Authorizied EXCURSION Dealers in Germany. Products purchased by consumers from an EXCURSION dealer in another country are covered only by that country's Distributor and not by EXCURSION Intl.

This warranty covers only the original purchaser of EXCURSION product. In order to receive service, the purchaser must provide EXCURSION with the receipt stating the consumer name, dealer, product and date of purchase.

Products found to be defective during the warranty period will be repaired or replaced (with a product deemed to be equivalent) at Excursion's discretion and will not be liable for incidental or consequential damages. EXCURSION will not warranty this product under the following situations:

- * Speakers received with bent frames or water damages
- * Abuse such as holes in the cone, surround or ripped spider
- * Voice coil damage due to amplifier clipping or distortion
- * Product that has not been installed according to this owner manual

Any implied warranties including warranties of fitness for use and merchantability are limited in duration to the period of the express warranty set forth above. No person is authorized to assume for EXCURSION any other liability in connection with the sale of this product.

Please call prior your authorizied EXCURSION dealer the product got purchased. In case they are not accessible call 0961-416-0420 for EXCURSION Customer Service. You must obtain an RA# (Return Authorization Number) to return any product to EXCURSION Intl. The RA number must be prominently marked on the outside of the shipping carton or the delivery will be refused. Please pack your return carefully! We are not responsibile for items damaged in shipping. Return the defective product along with a copy of the original dated retail sales receipt, plus 10,- EUR for handling and diagnostic evaluation to:

EXCURSION Intl. - A Division of CHPW Attn: Returns (RA#)
Neustaedter Str. 20
D-92685 Floss / Germany



EXCURSION - A Division of CHPW

All Rights reserved - Intl. Trademark No: 010 640 597

Friedrich-Ebert-Str. 42 - D-92637 Weiden / Germany Tel: (+49) 961-416 04 20 - Fax: (+49) 961-46 04 41



